

5KW FET Power PCB WG30Rev3 Issue 070225

Designator	Comment	Description	Footprint	Quantity	From	Cost	Comments
Blank PCB		WG30Rev3		1			
C1 - C6, 9, 11	1u	Monolithic or Film	2.54mm (0.2")	8			
C7, 8	1n5	Monolithic or Film	2.54mm (0.2")	2			
C10	22u 10V	Capacitor	0.2" or 0.1"	1			
D5	12V	Zener Diode	DO-35, (0.3")	1			
D6	5V1	Zener Diode	DO-35, (0.3")	1			
J1, J1A (J1A optional)	8 Way Pin Strip	Header strip	8 x 2.54mm/0.1"	1(2)			Install J1A if required for 2 Stage
L1 - L16	4mm OD, 1.3mm ID	FX1115 or equiv.	Ferrite Bead 5mmL		Farnell	9.4c	1633138
OC1 - OC4	8 PIN DIP Socket	Machined Pins	DIP8/300	4	Digikey		
(OC1 - OC4)	FOD3182	Opto/Gate Driver	DIP8/300	4	Digikey LCSC	2.28 0.??c	Gull wing SMD with adaptor PCB LCSC Part #C19185370
Q1 - Q8 Long Source Leg	HY5608W N Channel	Power MOSFET	TO-247H LSNG	8	LCSC	\$1.55	Needs TO220 Bush & TO247 SilPad
(Q1 - Q8)	Insulator & Sil Pad	TO220 Bush	3.56mm dia.	8	Digikey		12SWS0218 or 12SWS0428
Q9 - Q16 Long Drain Leg	HY5608W N Channel	Power MOSFET	TO-247H LDNG	8	LCSC	\$1.55	Needs TO247 SilPad insulator
(Q9 - Q16)	Silpad		To Suit TO247	8	Digikey		
Q18, 20, 22, 24	ZX5T951GQTC	PNP Transistor	TO-251AA/SOT223	4	LCSC	0.29c	
Ra - Rp	1R2 For Q1-Q16 Gates	0.6W resistor	Axial PCB to Gate	16			
R2, 3, 6, 7, 10, 11, 14, 15	1K	0.25-0.6W Axial	10mm (0.4" pitch)	8			
R4	100R	0.25-0.6W Axial	10mm (0.4" pitch)	1			
R17 - R20	120R	0.25-0.6W Axial	10mm (0.4" pitch)	4			
R24	1K	0.25-0.6W Axial	10mm (0.4" pitch)	1			
R26-R29	10K	0.25-0.6W Axial	10mm (0.4" pitch)	4			
T1 - T4	Screw Terminal 120A	PCB-5 M6 LCSC #14580400M5	Terminal M5/M6 120A	4	Ali LCSC		See note below 10 off 0.49c, 30 off 43.3c
T5, 7, 8, 10, 11, 13, 14, 16	Screw Terminal 33A	PCB-7 M4	Terminal M4 33A	8	Ali LCSC		
U1, 2, 3 (12V) (no bias)	DC-DC 2W	B1212M-2WR3	SPU01V	2 or 3	Digikey		or 2S4E_1212S1U
U3 (15V) with -3V bias	DC-DC 2W	2S4E_1215S1U	SPU01V	1 or 0	Digikey		or RI-1215S
U1A-3A (12V) (no bias)	DC-DC 2W	S12HIS12-2WH2	SPU02V	1 or 0	Digikey		or 2S7BE_1212S3U
U3A (15V) with -3V Bias	DC-DC 2W	S12HIS15-2WH2	SPU02V	1 or 0	Digikey		or 2S7BE_1215S3U

WG06 Rev 1 PCB (x2)

Blank PCB		WG06Rev1		2			
C1-C4	4,700u - 10,000u 63V	Snap In Electrolytic		2 to 8	Digi		

Associated Parts Comments

8 Way Ribbon Cable suggest ~ 200mm long, 2.54mm sockets each end to connect controller PCB to Power PCB

Choke ~ 30uH At least 200+A peak before saturation, best material Sendust, Hi Flux or similar.

I use only quality Machined Pin IC sockets (not Asian cheapies - they fail!) for the Optos, 4 x 8pin DIP

Insulating washers or insulating strip sheet for the 16 MOSFets (16 x HY5608) self adhesive type helps.

8 x TO220 insulating Bushes for Q1 - Q8 outer bush diameter 3.56mm (suits PCB Hole) 7721-10PPSG or equivalent

2 x lengths Aluminium bar 10mm x 25mm section, ~300mm Long, with 8 x M3 CSK FET holes & 3 x M4 Mount holes.

T1-T4 link for Ali 10 off (\$1.07ea) <https://www.aliexpress.com/item/33042908984.html>

T1-T4 link for Ali 5 off (\$1.50ea) <https://www.aliexpress.com/item/1005006747470675.html>

T1-T4 link for LCSC (10 off 49c 30 off 43.3c) https://www.lcsc.com/product-detail/PCB-Welding-Terminal_SAMZO-14580400M5_C32710809.html